




**Low Capacitance ESD Protection Diode**


**Features**

- Transient protection for high-speed data lines  
IEC 61000-4-2 (ESD) ±20kV (Contact)  
±20kV (Air)  
IEC 61000-4-4 (EFT) 40A (5/50 ns)  
Cable Discharge Event (CDE)
- Package optimized for high-speed lines
- Ultra-small package (1.0mm×0.6mm×0.5mm)
- Protects one data, control line
- Low capacitance: 0.25pF (Typical)
- Low leakage current
- Low clamping voltage
- Lead free in comply with EU RoHS  
2011/65/EU directives



**Mechanical Data**

- DFN1006 package
- Flammability Rating: UL 94V-0
- Packaging: Tape and Reel
- High temperature soldering guaranteed: 260°C/10s
- Reel size: 7 inch



**Applications**

- Serial ATA
- Desktops, Servers and Notebooks
- Cellular Phones
- MDDI Ports
- USB Data Line Protection
- Display Ports
- Digital Visual Interfaces (DVI)

**Ordering Information**

Part Number	Marking	Shipping	Reel
LTE10N05C01LBU-TR10	5B+code(U or L)	10000PCS Tape&Reel	7 inches

**Absolute Maximum Ratings** (Tamb=25°C unless otherwise specified)








Symbol	Parameter	Value	Units
V <sub>ESD</sub>	ESD per IEC 61000-4-2 (Contact)	±20	kV
	ESD per IEC 61000-4-2 (Air)	±20	
P <sub>PP</sub>	Peak Pulse Power (8/20μs)	100	W
T <sub>OPT</sub>	Operating Temperature	-55~125	°C
T <sub>STG</sub>	Storage Temperature	-55~150	°C

**Electrical Characteristics**(TA=25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V <sub>RWM</sub>	Reverse Working Voltage				5.0	V
V <sub>BR</sub>	Reverse Breakdown Voltage	I <sub>T</sub> = 1mA	6.0			V
I <sub>R</sub>	Reverse Leakage Current	V <sub>RWM</sub> = 5V			100	nA
V <sub>C</sub>	Clamping Voltage	I <sub>PP</sub> = 1A, t <sub>p</sub> = 8/20μs			13	V
		I <sub>PP</sub> = 4A, t <sub>p</sub> = 8/20μs		18	25	V
V <sub>CTLP</sub>	TLP Clamping Voltage	I <sub>PP</sub> = 8A IEC61000-4-2 Level 2 equivalent (±4kV Contact, ±8kV Air)		26		V
		I <sub>PP</sub> = 16A IEC61000-4-2 Level 4 equivalent (±8kV Contact, ±16kV Air)		38		V
C <sub>J</sub>	Junction Capacitance	V <sub>R</sub> = 0V, f = 1MHz		0.25	0.40	pF




### Characteristic Curves




**DFN-1006 Package Outline**

Unit: mm



SYMBOL	DIMENSIONS	
	MIN.	MAX.
D	0.550	0.650
E	0.950	1.050
L1	0.200	0.300
L2	0.200	0.300
b	0.450	0.550
e	0.650 TYP.	
A	0.450	0.550
A1	0.000	0.050
h	0.070	0.170

**DFN-1006 Suggested Pad Layout**




SYM	DIMENSIONS
	MILLIMETERS
X	0.60
Y1	0.50
Y2	0.30
Y3	0.80
Z	1.30

**Note:**

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$
3. The pad layout is for reference purpose only.


**Carrier Tape Dimensions**

Unit : mm




**Reel Dimensions**

Unit : mm



**Packaging**





Recommended Soldering Conditions



Recommended Conditions

Profile Feature	Pb-Free Assembly
Average ramp-up rate (T <sub>L</sub> to T <sub>P</sub> )	3°C/second max.
Preheat	
-Temperature Min (T <sub>S min</sub> )	150°C
-Temperature Max (T <sub>S max</sub> )	200°C
-Time (min to max) (t <sub>s</sub> )	60-180 seconds
T <sub>S max</sub> to T <sub>L</sub>	
-Ramp-up Rate	3°C/second max.
Time maintained above:	
-Temperature (T <sub>L</sub> )	217°C
-Time (t <sub>L</sub> )	60-150 seconds
Peak Temperature (T <sub>P</sub> )	260°C
Time within 5°C of actual Peak Temperature (t <sub>p</sub> )	20-40 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

## Important Notice and Disclaimer

Leading-Tech reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Leading-Tech makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Leading-Tech assume any liability for application assistance or customer product design.

Leading-tech does not warrant or accept any liability with products which are purchase or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Leading-Tech.

Leading-Tech products are not authorized for use as critical components in life support devices or systems without express written approval of Leading-tech.

## Version Update Information

Series NO.	Enactment/Revision Date	Effective Date	Version	Revision content	Revision Reason	Revision Person	Note
01	2024.03.16	2024.03.16	3.0	New File	/	Ding	