


## Surface Mount General Purpose Silicon Rectifiers

### Features

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Easy to pick and place
- Lead free in comply with EU RoHS 2011/65/EU directives



### Mechanical Data

- Case:SMAW
- Terminal:Leads solderable per MIL-STD-750 Method 2026
- Polarity:Color band denotes cathode end
- Mounting Position:Any



### Ordering Information

Part Number	Marking	Shipping	Reel
LTM7W	M7	8000PCS Tape&Reel	13 inches

### Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.  
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Rating	Symbol	LTM7W	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	1000	V
Maximum RMS voltage	$V_{RMS}$	700	V
Maximum DC blocking voltage	$V_{DC}$	1000	V
Maximum average forward rectified current	$I_{F(AV)}$	1	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	$I_{FSM}$	40	A
Maximum instantaneous forward voltage at 1A	$V_F$	1	V
Maximum DC reverse current <small><math>T_A=25^{\circ}C</math>  at rated DC blocking voltage  <small><math>T_A=125^{\circ}C</math></small></small>	$I_R$	1 50	$\mu A$
Typical junction capacitance (Note1)	$C_J$	15	pF
Typical thermal resistance (Note2)	$R_{\theta JA}$ $R_{\theta JC}$	100 20	$^{\circ}C/W$
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150	$^{\circ}C$

Note: (1) Measured at 1MHz and applied reverse voltage of 4.0V D.C.  
 (2) P.C.B. mounted with 0.2" x 0.2"(5.0mm x 5.0mm) copper pad areas.



## Characteristics Curves

Fig.1 Forward Current Derating Curve




Fig.2 Typical Instaneous Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance








Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



**Package Outline**

**Suggested Pad Layout**



**Carrier Tape Dimensions**

Unit : mm




**Reel Dimensions**

Unit : mm



**Packaging**





## Recommended Soldering Conditions



### Recommended Conditions

Profile Feature	Pb-Free Assembly
Average ramp-up rate (T <sub>L</sub> to T <sub>P</sub> )	3°C/second max.
Preheat	
-Temperature Min (T <sub>S min</sub> )	150°C
-Temperature Max (T <sub>S max</sub> )	200°C
-Time (min to max) (t <sub>s</sub> )	60-180 seconds
T <sub>S max</sub> to T <sub>L</sub>	
-Ramp-up Rate	3°C/second max.
Time maintained above:	
-Temperature (T <sub>L</sub> )	217°C
-Time (t <sub>L</sub> )	60-150 seconds
Peak Temperature (T <sub>P</sub> )	260°C
Time within 5°C of actual Peak Temperature (t <sub>p</sub> )	20-40 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

## Important Notice and Disclaimer

Leading-Tech reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Leading-Tech makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Leading-Tech assume any liability for application assistance or customer product design.

Leading-tech does not warrant or accept any liability with products which are purchase or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Leading-Tech.

Leading-Tech products are not authorized for use as critical components in life support devices or systems without express written approval of Leading-tech.

## Version Update Information

Series NO.	Enactment/Revision Date	Effective Date	Version	Revision content	Revision Reason	Revision Person	Note
01	2024.01.23	2024.01.23	1.0	New File	/	Ding	
02	2025.06.27	2025.06.27	1.1	Update packaging information	/	Ding	